

**EC625006**



**GRP POLYESTER ENCLOSURE SOLID  
DOOR 140 MODULES (5X28)  
620X810X320 mm**



Envolventes > Montaje en pared > Cuadrados de poliÉster estancos > Tableros > Caja/armario de distribución (vacío) > Puerta ciega

**Technical Symbols/Marks/Approvals**



**Estándares**

EN 62208

**Etim**

**GROUP EG000011 - Enclosures/cabinets**

**CLASS EC000261 - Enclosure/cabinet (empty)**

<b>Degree of protection (IP)</b>	IP66	<b>Material</b>	Other	<b>Material quality</b>	GRP (Glass fibre reinforced plastic)
<b>Surface finishing</b>	Untreated	<b>Colour</b>	Grey	<b>Impact strength</b>	IK10
<b>Width</b>	620 mm	<b>Height</b>	810 mm	<b>Depth</b>	320 mm
<b>With cover</b>	Sí	<b>RAL-number</b>	7035	<b>With mounting plate</b>	No
<b>Pre-stamping</b>	No	<b>EMC-version</b>	No	<b>Suitable for wall mounting</b>	Sí
<b>Couplable</b>	Sí	<b>Mounting plate depth-adjustable</b>	Sí	<b>Suitable for wall built-in</b>	No
<b>Pole fastening</b>	Sí	<b>With door</b>	Sí	<b>Number of doors</b>	1
<b>With glazed door</b>	No	<b>With ventilation door</b>	No	<b>With rear door</b>	No
<b>Number of locks</b>	2	<b>Transparent cover</b>	No	<b>Suitable for outdoor set-up</b>	Sí
<b>Pitched roof</b>	No	<b>Number of connector holes</b>	0	<b>Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890</b>	96 W
<b>Max. permitted load of the mounting plate according to IEC 62208</b>	80 kg				

### Documentation available for download

**Instruction booklet**  
Istruzioni\_625\_042  
3.pdf

**Certification**  
MI22-0079305-01a  
- ELETTRCANTALI  
SPA - HCI\_1 -  
TR\_625.pdf

**Certification**  
MI22-0079305-01b  
- ELETTRCANTALI  
SPA - pH -  
TR\_625.pdf

**Certification**  
MI22-0079305-01c  
- ELETTRCANTALI  
SPA - HCI\_3 -  
TR\_625.pdf

**Certification**  
MI22-0079343-  
01\_TR\_625.pdf

**Certification**  
Serie 625  
IMQ\_CA02.06897\_  
2024.pdf

**Brochure**  
Quadri Poliestere  
IT.pdf

**Brochure**  
Quadri  
Poliestere\_ENG.pdf

### Barcode



8053676570393  
**Unit**  
1 NR  
13.9 [kg]